



SERIES 05



# MURRAY AGRICULTURAL EQUIPMENT

## PRODUCT INFORMATION

### PASTURE



Aeration, levelling, breaking down and spreading of organic matter

### PASTURELAND HARROW SERIES 05 - IMPROVE YOUR PASTURE YIELD

The Murray Pastureland Harrow System is recommended for pasture establishment, maintenance and renovation applications. Ideal for breaking down and distributing animal manures and other organic matter evenly across the whole pasture, using a Series 05 will encourage pasture growth. This light duty harrow is suitable generally for pasture areas of less than 100 acres (40 hectares) and tows easily behind small and medium size tractors.

Murray Series 05 Pastureland Harrows utilise four rows of double-sided tripod tine units which slice through patts, clods and coarse vegetation. The tripod section is followed by heavy steel square chain mesh which further pulverises and spreads the manure and organic matter and revitalises the pasture. The "standard" single-mesh chain Murray Pastureland Harrow has 8 rows of chain complete with a spreader bar and drag weights. Where greater penetration and a more aggressive action is needed, the Murray "super" double-mesh chain Pastureland Harrow may be used, which has 15 rows of square chain mesh. The extra chain length and weight ensure a thorough processing of material.

The Murray Pastureland Harrow is available in six widths between 1.52 metres (5') and 6.1m (20') in "standard"/single-mesh and "super"/double mesh versions. Each set of Murray Pastureland Harrows is supplied complete with a steel drawbar.

The Series 05 Pastureland Harrows can be used in conjunction with the Murray Series 21 3-point linkage Harrow Hoist Frame for ease of transportation.

For larger field operations, Murray Agricultural Equipment manufactures the Series 20 Heavy Duty Pasture Harrow System.



TOP: Tripod tine section

BOTTOM: Chain mesh section

# PASTURE

## SPECIFICATIONS

- Tine Spacing 51mm (2")
- Tine Length 85mm (3 11/32") approx
- Centre to Centre of Front Hooks 305mm (12")
- Available in 2 chain mesh depths 0.76m (2'6") and 1.5m (5')



### COVERAGE: DEEP MESH CHAIN - STANDARD 0.76M (2'6")

	DRAG TYPE						
Model No.	5020	5006	5021	5022	5023	5024	5003
Coverage (m)	1.52	1.83	2.44	3.04	3.65	4.57	6.09
Coverage (ft' in")	5'	6'	8'	10'	12'	15'	20'
Weight (kg)	82	99	129	172	213	269	380

	LIFT TYPE					
Model No.	5025	5007	5026	5027	5028	5029
Coverage (m)	1.52	1.83	2.44	3.04	3.65	4.57
Coverage (ft' in")	5'	6'	8'	10'	12'	15'
Weight (kg)	132	147	179	222	263	332

### COVERAGE: DEEP MESH CHAIN - SUPER 1.5M (5')

	DRAG TYPE						
Model No.	5067	5008	5030	5031	5032	5033	5004
Coverage (m)	1.52	1.83	2.44	3.04	3.65	4.57	6.09
Coverage (ft' in")	5'	6'	8'	10'	12'	15'	20'
Weight (kg)	123	133	173	225	292	349	490

	LIFT TYPE					
Model No.	5068	5009	5034	5035	5036	5037
Coverage (m)	1.52	1.83	2.44	3.04	3.65	4.57
Coverage (ft' in")	5'	6'	8'	10'	12'	15'
Weight (kg)	170	185	230	280	347	417

Contact your local farm machinery dealer for more information